



Commercial Oil Company of Hamilton Inc.

LUBRIKO®

LUBRIKO® WAX OIL

Description

Lubriko® Wax Oil is a unique blend of wax and oil compounded to inhibit rust. This product is ideal for older vehicles that may have rust developing, as it will deeply penetrate the rust and crevices with its capillary capabilities.

Lubriko® Wax Oil is a light tan colour and best applied using an airless spray system especially for the underbody of a vehicle. For the topside, doors, trunk, hood and engine compartment a fogging method is recommended.

Typical Properties

Colour		Light Tan
Weight per gallon		approx. 8 lbs.
Solids %		None
Viscosity, cSt	@40°C	46
Flash Point		220 °C
Solvent		None
Consistency		Fluid

Not a controlled product under WHMIS

Application

The vehicle should be clean and dry prior to spraying. There is no need to stir the product as the wax is held in suspension. When spraying, a single pass should be adequate; a double pass could cause excessive dripping. Avoid spraying any rubber or plastics.

Precautions

- When spraying use adequate ventilation, as vapours can be a health hazard.
- Using a respirator is recommended.
- If ingested, do not induce vomiting. Seek medical attention immediately.
- Read Material Safety Data Sheet before using.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.