



# Commercial Oil Company of Hamilton Inc.

## LUBRIKO®

### LUBRIKO® SPRAY OILS WITH TAC

#### Description

Lubriko® Spray Oils with Tac are formulated from highly refined base stocks fortified with rust and oxidation inhibitors. A tacifying agent is added to provide improved adhesion. A minimum yearly application is recommended. For spraying, an airless system is recommended but most systems are adequate, including brushing or dipping.

#### Typical Properties

Viscosity grades	22	46	68	100
Colour	Clear	Clear	Clear	Clear
Solids %	None	None	None	None
Viscosity @ 40°C cST	22	46	68	100
Flash Point °C COC	170	200	210	220
Consistency	Tacky Fluid	Tacky Fluid	Tacky Fluid	Tacky Fluid

#### Application

The vehicle should be clean and dry prior to spraying. When spraying a single pass should be adequate, a double pass could cause excessive dripping. The fogging method is recommended for doors, trunk and hood. Avoid spraying rubber, plastic, fibreglass components due to possible damage.

#### Precautions

- When spraying, use adequate ventilation as vapours can be a health hazard.
- Use of a respirator is recommended.
- If ingested, do not induce vomiting. Seek medical attention immediately.
- Read MSDS prior to using.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6  
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • [www.commercialoil.ca](http://www.commercialoil.ca)