



Commercial Oil Company of Hamilton Inc.

LUBRIKO®

LUBRIKO® DRIPLESS BLACK

Description

Lubriko® Dripless Black is a coating designed to protect the underbodies of vehicles against atmospheric corrosion and road salt. When properly applied, this product will not drip and is highly resistant to wash-off. This coating will not firm up like an OEM type.

Lubriko® Dripless Black is a black viscous fluid. Ideally an airless spray system is recommended but other conventional spray systems would do the job. This product should be applied on an annual basis.

Typical Properties

Colour	Black
Weight per 4 litres	approx. 3.63 kgs.
Flash Point C° COC	200 °
Thickener	Lithium
Solvent	None
Consistency	Light Greasy Film
Corrosion Resistance Salt Fog ASTM B-117	288 hrs.

Not a controlled product under WHMIS

Application

Prepare metal surfaces by removing excess dirt and moisture. A slightly oily surface is acceptable but discernible films should be removed. Stir material to ensure uniformity. Avoid spraying all rubbers or rubber moldings.

Precautions

- Oil vapours are harmful.
- The applicator should wear breathing protection and spray in a well-ventilated area.
- See Material Safety Data Sheet for further information.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.