



Commercial Oil Company of Hamilton Inc.

LUBRIKO®

LUBRIKO® DRIPLESS AMBER

Description

Lubriko® Dripless Amber is a coating designed to protect the underbodies and topsides of vehicles against atmospheric corrosion and road salt. When properly applied, this product will not drip and is highly resistant to wash-off. The coating will not completely dry but will form a tacky finish on metal surfaces.

Lubriko® Dripless Amber is a light amber viscous fluid containing water displacing surfactants and creeping agents. Application by airless spray system is recommended but other conventional spray systems can be successfully used. This product should be applied on an annual basis.

Typical Properties

Colour	Light Amber
Weight per 4 litres	approx. 3.63 kgs.
Flash Point	200 °C
Thickener	Calcium
Solvent	None
Consistency	Light Greasy Film
Corrosion Resistance Salt Fog ASTM B-117	288 hrs.

Not a controlled product under WHMIS

Application

Prepare metal surfaces by removing excess dirt and moisture. A slightly oily surface is acceptable but discernible films should be removed. Avoid spraying all rubbers or rubber moldings.

Precautions

- Oil vapours are harmful.
- The applicator should wear breathing protection and spray in a well-ventilated area.
- See Material Safety Data Sheet for further information.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.