

Commercial Oil Company of Hamilton Inc.

SN MULTI GRADE MOTOR OILS

Description

Lubriko[®] SN Series Motor Oils are available in three multi viscosity grade formulations. These synthetic blend motor oils meet the latest automotive and light duty truck manufacturers' requirements, API SN and ILSAC GF-5. Lubriko[®] Motor Oils utilize high quality virgin base oils combined with the latest in additive technology. These products provide the highest levels of equipment protection available.

Usage

Lubriko® SN Motor Oils are generally used in gasoline and light duty diesel engine applications. The product is available in 5W20, 5W30, 10W30 viscosity grades. Users should follow equipment manufacturer recommend-dations for specific applications

Typical Properties

Kinematic	5W20	5W30	10W30
Viscosity, cST @ 40°C	48.5	63.0	69.0
@ 100°C	8.6	10.5	10.6
Viscosity Index	156	156	142
Cold Crank (cP)	5800@-30C	6200@-30C	6200@-25C
Pour Point °C	-47	-47	-35.6
Density @ 15°C, kg/m3	.868	.87	.878

Application

Lubriko® SN Motor Oils may be recommended for the following applications:

- When SN, SM, SJ, SH, SF, SE, SD, or SC oils are required
- When GM 4718M/6094** and Ford M2C153-E oils are required
- When Energy Conserving (ILSAC GF-5) motor oil is specified.
- Meets foreign and domestic car manufacturers' requirements.

Product Features

- Excellent protection from deposits at all operating temperatures
- Excellent bearing corrosion protection
- Excellent anti-wear, anti-foam and anti-rust properties
- Excellent cold cranking capabilities

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.