



Commercial Oil Company of Hamilton Inc.

LUBRIKO®

LUBRIKO® SLUSHING OIL P1011RP

Description

Lubriko® Slushing Oil P1011 RP is a mineral oil thin film rust preventative that is free of barium and heavy metals. It is non-staining, so treated metals can be stacked or coiled without blemish. It's exceptional salt spray performance makes it ideal for treating metals that are to be shipped overseas or warehoused near the ocean.

Typical Properties

Flash Point, °C (COC)	ASTM D-92	177.0
Specific Gravity @ 15.6°C	ASTM D-1298	0.840
Viscosity, cSt @ 40°C	ASTM D-445	8.5-10.5
Colour	Visual	Amber
Salt Spray Performance	ASTM B117	>24 hours

Application

Lubriko® Slushing Oil P1011RP can be applied directly to pickled steel either by dip or spray. Please consult the Material Safety Data Sheet for further health and safety information.

Product Features

- Cost effective rust preventative.
- Exceptional salt spray/humidity protection
- Superior water separating properties.
- Free of barium and other heavy metals.
- Non-corrosive to a variety of non-ferrous metals

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.