



Commercial Oil Company of Hamilton Inc. **LUBRIKO®**

MULTI-MIX 2-STROKE OIL

Description

Lubriko® Multi-Mix 2-Stroke Oil is formulated using the latest advanced ashless additive system and is suitable for all types of 2-stroke motors. This product protects against excessive wear and deposit formation thereby providing peak performance and long engine life. It also contains an enhanced lubricity booster which allows for reduced oiling rates and surpasses the 2004 AF-27 lubricity test.

Usage

Lubriko® Multi-Mix 2-Stroke Oil is suitable for use in both carburetted and Direct Fuel Injection (DFI) outboards. In two stroke engines calling for TC-W3 (1995), TC-WII (1989) and TC-W (1970) quality engine oil.

Typical Properties

Flash Point °C (D93)	90
Pour Point °C	-30
Kinematic Viscosity, cST @ 40°	47
@ 100°	7.7
Viscosity Index	131
Sulphated Ash, %	<.001
TBN, mg KOH/g (D2896)	6.05
Brookfield @ -25°C cP	5520/Pass

Benefits

- Longer engine life than conventional TC-W3 two strokes
- Ashless technology reduces spark plug fouling and pre-ignition
- Upper piston detergency reduces potential for piston ring stick
- Enhanced lubricity booster to perform at reduced oiling rates recommended for DFI engines

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • www.commercialoil.ca