

LOW VISCOSITY AUTOMATIC TRANSMISSION FLUID

Description

Lubriko® **Low Viscosity ATF** is a low viscosity, multi-vehicle fully synthetic automatic transmission fluid engineered for use in today's modern automatic transmissions, including GM's new Hydra-Matic 6L80 transmission. **Lubriko**® **Low Viscosity ATF** is formulated with the highest quality base stocks as well as a state-of-the-art additive package that ensures oxidation stability, shear stability, and provides excellent low temperature fluidity. **Lubriko**® **Low Viscosity ATF** is a low viscosity formulation that meets the latest OEM requirements for 5, 6 and 7. **Lubriko**® **Low Viscosity ATF** provides exceptional friction durability as required by the Dexron VI specification, providing smooth operation over the life of the vehicle.

Features and Benefits

- GM Approved
- Low Viscosity
- Excellent Low Temperature Properties

- Outstanding Oxidation Stability
- Exceptional Shear Stability
- Excellent Wear Protection

Typical Properties

| Density | kg/m³ | 855 | Viscosity Index | 177 |
|-----------------------|-------------|-------|-------------------------|-------|
| Viscosity | cSt @ 100°C | 5.97 | Specific Gravity | 0.847 |
| Brookfield Viscosity, | | | Density lbs/gal @ 60 °F | 7.052 |
| D-2983 | cP @ -40°C | 11500 | Colour | Red |

Applications

- Dexron VI, Dexron IIIH
- Mercon LV
- Toyota WS

- Nissan Matic S
- Hyundai SP-IV
- Mercedes 7 Speed

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.