



LUBRIKO®
RUST PREVENTATIVE 1000 RT

Description

Lubriko® Rust Preventative 1000 RT is an oil based, light film rust preventative designed for indoor or short term applications. The residual film provides resistance to high humidity and salt environments.

Usage

Lubriko® Rust Preventative 1000 RT is ideal for coating parts and materials before being shipped or between manufacturing processes. It can be applied by brush, spray or dipping. The film will remain wet and can be removed by alkaline washer or by hand.

Features and Benefits

Lubriko® Rust Preventative 1000 RT is ideal for short term applications because of its ease of application and removal. It will afford short term rust protection indoors and out.

Typical Properties

Viscosity cST 40°C	100
Total Base Number, mg KOH/gm, ASTM D-664	.28
Specific Gravity @ 15.6°C ASTM D-1480	.88
Pounds per Gallon @ 15.6°C	7.33
Flash Point, deg. C, TCC	200°C
Nonvolatile, wt. %, ASTM D-2369	90-96
Colour	Light

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • www.commercialoil.ca