LUBRIKO®
HYDRAULIC OIL (ANTI – WEAR) AW 22

Description

Lubriko® Hydraulic Oil AW 22 is formulated using only the highest quality base oils and additives. It is premium quality hydraulic oil suitable for severe duty service.

Usage

Recommended for use in both high and low pressure industrial and mobile hydraulic systems, **Lubriko® Hydraulic Oil AW 22** is approved for applications in food production where there is no direct food contact. For extreme low temperature applications see **Lubriko® MV** series hydraulic oils. For non-flammable hydraulic oils, please see **Lubriko® Safety Hydraulic Fluid**.

Typical Properties

Flash Point COC °C		170
Pour Point °C		-39
Density @ 15°C, kg/L		.870
Kinematic Viscosity, cSt	@40°	22.0
	@ 100°	4.35
Viscosity Index		92
Colour (ASTM)		1.0
Rust Test, (ASTM D665) 24 Hrs. @ 60°C		
Distilled Water		Pass
Synthetic Sea Water		Pass

Applications

Lubriko® Hydraulic Oil AW 22 meets the latest pump manufacturer's requirements including Hagglund-Denison HF-0, HF-1, HF-2 and Cincinnati Milacron P-68, P-69 and P-70 specifications for anti wear hydraulic oils. This product is not suitable for PM-500 series silver containing pumps which require R&O additive systems**.**

Features and Benefits

- Proven field performance
- Outstanding thermal and oxidative stability
- Excellent demulsability
- Excellent rust protection

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • www.commercialoil.ca