



## **LUBRIKO®** **HYDRAULIC OIL (ANTI – WEAR) AW 32**

### **Description**

**Lubriko® Hydraulic Oil AW 32** is formulated using only the highest quality base oils and additives. It is premium quality hydraulic oil suitable for severe duty service.

### **Usage**

Recommended for use in both high and low pressure industrial and mobile hydraulic systems, **Lubriko® Hydraulic Oil AW 32** is approved for applications in food production where there is no direct food contact. For extreme low temperature applications see **Lubriko® MV** series hydraulic oils. For non-flammable hydraulic oils, please see **Lubriko® Safety Hydraulic Fluid**.

### **Typical Properties**

Flash Point COC °C		200
Pour Point °C		-39
Density @ 15°C, kg/L		.870
Kinematic Viscosity, cSt	@ 40°	32.0
	@ 100°	5.45
Viscosity Index		105
Colour (ASTM)		1.0
Rust Test, (ASTM D665) 24 Hrs. @ 60°C		
Distilled Water		Pass
Synthetic Sea Water		Pass

### **Applications**

**Lubriko® Hydraulic Oil AW 32** meets the latest pump manufacturer's requirements including Hagglund-Denison HF-0, HF-1, HF-2 and Cincinnati Milacron P-68, P-69 and P-70 specifications for anti wear hydraulic oils. This product is not suitable for PM-500 series silver containing pumps which require R&O additive systems.

### **Features and Benefits**

- Proven field performance
- Outstanding thermal and oxidative stability
- Excellent demulsability
- Excellent rust protection

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification

**35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6**  
**905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • [www.commercialoil.ca](http://www.commercialoil.ca)**