



# Commercial Oil Company of Hamilton Inc.

## **LUBRIKO®**

### LUBRIKO® VANISHING OIL

#### Description

Lubriko® Vanishing Oil is an outstanding water displacing, non-staining rust preventative, which will rapidly separate water from metal surfaces, after machine operations or after alkali cleaning.

#### Usage

Lubriko® Vanishing Oil is effective for indoor protection of ferrous and non-ferrous metals from atmospheric corrosion, even under conditions of high humidity. Not recommended for outdoor protection.

#### Typical Properties

Physical State	Liquid
Vapour Pressure	1.3 Kpa @ 38°C
Vapour Density (air = 1)	4.9
Evaporation Rate	0.11
Volatile %	90
Colour	Brown Liquid
Solvent %	90
Solids %	10

#### Application

Lubriko® Vanishing Oil can be applied by dipping, brushing or spraying. The solvent will evaporate quickly, leaving a dry oxidation inhibited surface.

#### Precautions

- Vapours are harmful and flammable.
- The applicator should wear a respirator and apply product in a well ventilated area..
- Read Material Safety Data Sheet before using.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.