



# Commercial Oil Company of Hamilton Inc.

## **LUBRIKO®**

### LUBRIKO® HEAT TRANSFER OIL 100

#### Description

Lubriko® Heat Transfer Oil 100 contains an oxidation inhibitor and detergent package to provide long service life at elevated bulk system temperatures with associated high "skin" temperatures. The oxidation inhibitor will offer a long service life. The detergent package provides system cleanliness.

#### Typical Properties

|                                      |  |
|--------------------------------------|--|
| Viscosity @ 40cTs °C                 | 100.10                                     |
| Viscosity @ 100 cTs ° C              | 10.90                                      |
| Pour Point ° C                       | -12°C                                      |
| Flash Point COC °C                   | 245°C                                      |
| Max recommended bulk oil temperature | 215°C Open Systems<br>315°C Closed Systems |
| Max recommended skin temperature     | 340°C                                      |
| Minimum pump start up temperature    | 5°C  |

#### Usage

Lubriko® heat transfer fluids are highly recommended in applications that require indirect heat transfer either in open or closed systems.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.