



Commercial Oil Company of Hamilton Inc.

LUBRIKO®

SLIDEWAY LUBRICANTS

LUBRIKO® WAY GOLD 68 & 220

Description

Lubriko® Way Gold 68 and Way Gold 220 are formulated specifically as machine tool way oils. These products ensure enduring lubrication under both sparse and flood lubricated conditions.

Usage

Lubriko® Way Gold 68 is suitable for use as a slideway lubricant where a medium to heavy viscosity oil is specified.

Lubriko® Way Gold 220 is recommended for similar applications but where a heavy viscosity is required.

Typical Properties

	Way Gold 68	Way Gold 220
Pour Point °C	-27.0	-12.0
Flash Point (COC) °C	194.0	230.0
Viscosity cSt @ 40°C	68.8	220.0
Viscosity cSt @ 100°C	7.97	18.4
Colour	2.0	2.5

Application

Lubriko® Way Gold contains special additives designed to provide the necessary qualities to protect against stick-slip. This will eliminate chatter and scoring in the operation of machine tool slideways.

Lubriko® Way Gold is formulated to meet the requirements of Cincinnati Milacron specifications P-47 and P-50

Product Features

- Strong demulsability and water separation characteristics.
- Special non-corrosive additives
- Excellent metal wetting and EP characteristics
- Suitable for copper and aluminum
- Non-staining
- Extra tackiness and rust protection
- Phosphorous free chemistry
- Ashless light colour technology
- Passes Bijur stringent filtration test requirements.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • www.commercialoil.ca