



## **LUBRIKO®**

### **CONCRETE RELEASE 709**

#### **Description**

Concrete Release 709 is a ready to use mixture of process oils and naturally derived chemical release agents that prevent bonding of concrete to form.

#### **Features and Benefits**

For use on all types of forms; including wood, steel, aluminum, fiberglass and plastic. Can be used daily on equipment and tools to prevent or soften concrete buildup.

#### **Typical Properties**

Flash Point		160 °C
Cloud Point		-20 °C
Pour Point		-20 °C
Colour (ASTM)		1.0 – 2.0
Viscosity, cSt	@40°C	8.5 – 10.0
Staining		None

#### **Applications**

Surfaces should be clean of hardened concrete. On steel forms, remove rust and residues to ensure best results. Applied using low-pressure sprayer, to ensure a light, even coating. When applying via brush, roller, or sponge care should be taken to apply as thinly as possible to guarantee good results. Forms should be re-coated before each use.

#### **Product Features**

- Concrete Release 709 does not contain “diesel” or solvents and is extremely user and environmentally friendly.
- Concrete Release 709 is not governed by WHMIS laws.
- Increases life of wooden forms and reduces rust on steel forms when in storage.
- Does not discolor or stain concrete.
- These are cost effective products for a wide range of concrete forming applications

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification

**35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6**  
**905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • [www.commercialoil.ca](http://www.commercialoil.ca)**