



LUBRIKO® LITHIUM EXTREME PRESSURE GREASE

Description

Lubriko Lithium Extreme Pressure Greases are high quality lithium soap greases. They will provide excellent lubrication over a wide range of operating temperatures under wet, dry or dusty conditions.

Typical Properties

	EP00	EP-0	EP-1	EP-2
Colour, appearance	Dark	Dark	Dark	Dark
Texture	Smooth	Smooth	Smooth	Smooth
Timken OK Load, kg,	23	24	26	30
Rust Prevention Test,	Pass	Pass	Pass	Pass
Dropping Point, °C ASTM D 2265	160	160	180	180
Viscosity of Base Oil	cSt @ 40°C	162	176	176
	cSt @ 100°C	13	15	15
Lithium Hydroxy Stearate	12%	12%	12%	12%

Usage

Lubriko Lithium Extreme Pressure Greases combine good high temperature properties with excellent water resistance. The extreme pressure agent used provides the added lubrication required to handle severe conditions characterized by high shock loads on bearings. These greases satisfy a wide range of fleet, industrial and farm machinery applications including bearings, ball joints and bushings. **Lubriko Lithium Greases** are available in NLGI Grades 0, 1, and 2 and as a semi fluid.

Applicaton

The service temperature range of these greases is -29°C (-20°F) to 120°C (250°F) continuous, with peak intermediate temperatures up to 150°C (300°F). For higher operating temperatures please refer to **Lubriko Lithium Complex High Temperature Greases**.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • www.commercialoil.ca