

Commercial Oil Company of Hamilton Inc. **LUBRIKO**®

COMPRESSOR OILS

Description

Lubriko® Compressor Oils are formulated from highly refined paraffinic base oils. Their high natural thermal and oxidative stability have been further enhanced by a top quality additive system for the lubrication of rotary and reciprocating air compressors.

Usage

Each grade of compressor oil when used within its appropriate recommended application temperature and viscosity ranges will provide a range of benefits including;

- Outstanding cylinder and piston ring lubrication
- Excellent lubrication of timing gears and bearings in rotary compressors
- Reduced build-up of carbon on discharge valves and inter-coolers
- Long oil life in circulating systems and crankcases
- All grades are rust and oxidation inhibited
- Excellent water separation (demulsibility)

Petroleum oils are not recommended for compressors supplying breathing air. Non-lubricated or 'oilless' compressors are preferable for this application.

Lubriko® Compressor Oils meet the USDA requirements of an H2 lubricant where no food contact will occur.

Typical Properties

	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150
Pour Point °C	-18	-14	-12	-6	-1
Flash Point °C	200	204	208	225	235
Viscosity cSt @ 40°C	32	46	68	100	150
Viscosity cSt @ 100°C	5.3	6.8	8.5	11.1	14.2
Viscosity Index	100	100	95	95	90
ASTM Test (Rust)	Pass	Pass	Pass	Pass	Pass

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.