



# SAFETY DATA SHEET

Lubrisol GP 478

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Lubrisol GP 478  
**SUPPLIER:** Commercial Oil Company  
P (905) 560-3244  
F (905) 560-2961  
35 Burford Road  
Hamilton, Ontario  
L8E 3C6

**WHMIS:** Controlled - Class D, Division 2B-Toxic

Product and SDS Information: 1-800-463-1976

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

**Aspiration hazard: Category 2**

### GHS label elements

**Hazard pictograms:**



**Signal word: Danger**

**Hazard statements: May be fatal if swallowed and enters airways.**

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance/Mixture: Mixture**

Chemical Name	CAS – No.	Concentration
Hydro-treated Mineral Oil	8042-47-5	20-40%

## SECTION 4. FIRST AID MEASURES

**INHALATION:** Avoid breathing product mists. If over exposed to oil mist, remove from further exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

**EYE CONTACT:** May cause mild irritation. Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:** Flush with large amounts of water. Use soap if it is available. Remove severely contaminated clothing (including shoes) and launder before reuse. If irritation persists, seek medical attention.

**INGESTION:** If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

## SECTION 5. FIRE-FIGHTING MEASURES

**Flashpoint and method:** 277 deg C COC

**Auto ignition:** NA **Flammable Limits:** LEL NA **UEL:** NA

This product is considered non-combustible due to its high water content

**.GENERAL HAZARDS:** Low hazard; liquids may burn upon heating to temperatures at or above the flash point. Decomposes; flammable/toxic gases will form at elevated temperatures (thermal decomposition). Toxic gases will form upon combustion. Empty product containers may contain product residue. Do not pressurize, cut, heat, weld, or expose containers to flame or other sources of ignition.

**FIRE FIGHTING:** Use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to fire. Use foam, dry chemical or water spray to extinguish fire. Respiratory and eye protection required for fire fighting personnel. Avoid spraying water directly into storage containers due to danger of boil over. A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an SCBA may not be required.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**NOTIFICATION PROCEDURES:** Report spills as required to appropriate Provincial and Federal authorities. In particular, immediate reporting is required for all spills that could reach any waterway, including wetlands and intermittent dry creeks.

**LAND SPILL:** Eliminate source of ignition. Keep public away. Prevent additional discharge of material; if possible do so without hazard. Prevent spills from entering sewer watercourses or low areas. Contain spilled liquid with sand or earth. Recover by pumping or using a suitable absorbent. Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse affects of the spill.

**WATER SPILL:** Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in unconfined waters. Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all action necessary to prevent and remedy the adverse affects of the spill.

PERSONAL PRECAUTIONS: See Section 8

## SECTION 7. HANDLING AND STORAGE

**HANDLING STORAGE AND SHIPPING:** Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**PERSONAL PROTECTION:** The selection of personal protective equipment varies depending upon conditions of use. Where prolonged and/or repeated skin and eye contact is likely to occur, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where eye contact is unlikely, but may occur as a result of short and/or periodic exposures, wear safety glasses with side shields. Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

**ENGINEERING CONTROLS:** The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation in a confined space.

**SKIN PROTECTION:** Wear gloves when handling.

**ENGINEERING CONTROLS:** The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation in a confined space.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid

**Boiling Point:** 92°C

**pH:** 9.2 in 10 % water solution

**Refract meter Conversion Factor:** 1 Brix = 1.0 %

**Evaporation Rate:** <1 (1=n-butyl acetate)

**Specific Gravity:** .95

**Appearance:** Clear Amber Colour

## SECTION 10. STABILITY AND REACTIVITY

**STABILITY:** This product is stable. Hazardous polymerization will not occur.

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:** Strong oxidizing agents. Acids

**HAZARDOUS DECOMPOSITION:** Decomposition products are highly dependent on the combustion conditions. Significant concentrations of hazardous decomposition products are not expected.

## SECTION 11. TOXICOLOGICAL DATA

### ORAL TOXICITY

Low acute toxicity.

### DERMAL TOXICITY

Repeated exposure may cause skin dryness or cracking.

### INHALATION TOXICITY

Negligible hazard at normal temperatures (up to 38 deg C). Elevated temperatures or mechanical action may form vapours, mists or fumes, which may be irritating to the eyes, nose, throat and lungs. Avoid breathing vapours or mists.

### EYE IRRITATION

Slightly irritating but will not injure eye tissue

### SKIN IRRITATION

Practically non-irritating. (Primary Irritation index: greater than 0.5 but less than 3). Based on testing of similar products and/or the components.

## SECTION 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL FATE AND EFFECTS:** Dangerous for the environment if discharged into watercourses.

## SECTION 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** The product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

## SECTION 14. TRANSPORT INFORMATION

**PRODUCT LABEL ...** Lubrisol GP 478

**CATEGORY :** II

**UN # :** 3082

**SHIPPING NAME.....**Not Regulated by DOT

## SECTION 15. REGULATORY INFORMATION

No information available.

## SECTION 16. PREPARATION

**USE:** Lubricant

COMMERCIAL OIL COMPANY  
Hamilton, Ontario

**Date:** November 16, 2018  
**Prepared by:** Operations

---

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.